

CODE NUMBER

11070001

DESCRIPTION

Vitreous China Washdown Urinal.

DETAILS

- Flush volume determined by the flushometer used with the fixture
- Nominal Dimensions: 14 ¾" × 14 ⅜" × 23 ½" (375 × 360 × 597mm)

FEATURES

- Designed to maximize and complement Sloan flushometers
- Small size and clean lines fits a large variety of applications and restroom looks
- Thorough washdown flushing action
- Durable, hygienic vitreous china construction
- Vandal resistant stainless steel strainer included

PLUMBING SYSTEM REQUIREMENTS

- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)
- Maximum Flow Rate: 8.5 gpm (32 Lpm)

DOWNLOADS

- [SG-7019 Installation Instructions - India](#)
- [SG-7019 Repair & Maintenance Guide](#)
- [Fixture Full Line Brochure \(India\)](#)

**NOTES**


All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

WaterSense compliant when used with a WaterSense compliant flushometer.

[Find a compatible flushometer](#) for this urinal.

ROUGH-IN



NOTE: ADA urinal rim height requirements allow all heights 17" and below. Sloan strongly recommends roughing in the drain to achieve a 16½" rim height or less to ensure compliance.