

OPTIONS**Power Type**

Solar

Body Type

High

Mounting

Deck

Power Supply

Solar (SOL)

Sensor Type

Infrared (IR)

Flow Rate

0.5 gpm (2 Lpm) (0.5GPM)

1.5 gpm (6 Lpm) (1.5GPM)

Spray Type

Aerated (installed) or Laminar (in box)

Multi-Laminar (MLM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Mixer Not Included

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

Proposition 65

TAS

UPC Certified


UPC Low Lead Compliant

cUPC Certified

cUPC Low Lead Compliant

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change

**DESCRIPTION**

BASYS® Solar-Powered Deck-Mounted High Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-114
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

without notice.


[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

DOWNLOADS

- [EFX 1Xx/2Xx Installation Instructions](#)
- [EFX 1Xx/2Xx \(SP\) Installation Instructions](#)
- [EFX 1Xx/2Xx Caddy Replacement Installation Instructions](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [EFX-1XX Repair and Maintenance Guide](#)
- [Trim Plate Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [BASYS[®] Faucet Installation and Features](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com