

OPTIONS**Sensor Type**

Infrared
Capacitance (CAP)

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM)
0.5 gpm (1.9 Lpm) (0.5GPM)

Spray Type

Multi-Laminar (MLM)
Aerated (installed) or Laminar (in box)

Control Access

Below Deck
Above Deck

Mixer

Back-Check Tee (TEE)
Below Deck Thermostatic Mixing Valve (BDT)
Below Deck Manual Mixing Valve (BDM)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.



Image for a standard EFX-650 shown

DESCRIPTION

BASYS® Battery-Powered Deck-Mounted Low Integrated Base Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Integral 4-inch base
- Includes all mounting hardware
- Line Purge mode, eliminates stagnant water
- 3 year limited warranty

DOWNLOADS

- [EFX 3Xx/6Xx Active IR Installation Instructions](#)
- [EFX 3Xx/6Xx Active IR \(SP\) Installation Instructions](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- [Trim Plate Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [EFX-6XX Repair and Maintenance Guide](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [BASYS® Faucet Installation and Features](#)
-  [Sloan Connect App®](#)