SLOAN.

OPTIONS

Power Supply

Plug Adapter (PLG) Hardwired Less Transformer (HLT) Box Transformer (BOX)

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM) 0.5 gpm (1.9 Lpm) (0.5GPM)

Spray Type

Aerated (installed) or Laminar (in box) Multi-Laminar (MLM)

Mixer

Back-Check Tee (TEE) Below Deck Manual Mixing Valve (BDM) Below Deck Thermostatic Mixing Valve (BDT)

Special Features

Lithium Batteries

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



Image for a standard EFX-800 shown

DESCRIPTION

BASYS® Hardwired-Powered Wall-Mounted Wall Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components are stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral above deck water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Bi-stable magnetic solenoid
- One (1) CR-P2 battery
- Double infrared sensors with automatic setting feature
- Optional Wall Flange included
- Line Purge mode, eliminates stagnant water
- Adjustable time-outs and sleep/cleaning mode
- Sleep/cleaning Mode
- Includes all mounting hardware
- 3 year limited warranty

DOWNLOADS

- EFX 8Xx Installation Instructions
- EFX 8Xx (SP) Installation Instructions
- EFX 1009-A/1010-A/1018-A Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-8XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads

VIDEOS

BASYS® Faucet Installation and Features

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com