SLOAN.

OPTIONS

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM) 1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM) Aerated (installed) or Laminar (in box)

Mixer

Back-Check Tee (TEE) Below Deck Thermostatic Mixing Valve (BDT) Below Deck Manual Mixing Valve (BDM)

Special Features

Lithium Batteries

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

BASYS® SENSOR FAUCET EFX-850



Image for a standard EFX-850 shown

DESCRIPTION

BASYS® Battery-Powered Wall-Mounted Wall Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components are stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral above deck water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Bi-stable magnetic solenoid
- One (1) CR-P2 battery
- Double infrared sensors with automatic setting feature
- Optional Wall Flange included
- Line Purge mode, eliminates stagnant water
- Adjustable time-outs and sleep/cleaning mode
- Sleep/cleaning Mode
- Includes all mounting hardware
- 3 year limited warranty

DOWNLOADS

- EFX 8Xx Installation Instructions
- EFX 8Xx (SP) Installation Instructions
- EFX 1009-A/1010-A/1018-A Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-8XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads

VIDEOS

BASYS® Faucet Installation and Features

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com