# SLOAN.

#### OPTIONS

#### **Power Type**

Hardwired

#### **Body Type**

Mid

#### Mounting

Deck

# **Power Supply**

Plug Adapter (PLG) Hardwired Less Transformer (HLT) Box Transformer (BOX)

#### Sensor Type

Infrared

# Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM) 1.5 gpm (5.7 Lpm) (1.5GPM)

## Spray Type

Multi-Laminar (MLM) Aerated (installed) or Laminar (in box) Laminar (LAM)

#### Trim Plate

None 4" (102mm) (4) 8" (203mm) (8)

## Finish

Polished Chrome (CP) Brushed Nickel (BN) Polished Brass (PB) Brushed Stainless (SF)

## **Control Access**

Above Deck

## Mixer

Integrated Side Mixer (ISM) Back-Check Tee (TEE) Below Deck Thermostatic Mixing Valve (BDT) Mixer Not Included Below Deck Manual Mixing Valve (BDM)

## **Special Features**

Drain Pop Up (DPU) Carbon Offset (CO)



Image for a standard EFX-200 shown

## DESCRIPTION

BASYS® Hardwired-Powered Deck-Mounted Mid Body

#### FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



#### **Compliances & Certifications**

ADA Compliant ASME A112.18.1 Compliant CEC Compliant EPD HPD Proposition 65 TAS UPC Certified UPC Low Lead Compliant WELL Building Standard

#### NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

#### DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx (SP) Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads

# VIDEOS

- BASYS® Faucet Installation and Features
- BASYS® Faucet Installation Mid Height Model
- Sloan Connect App®