



NETZSCH PERIPRO Peristaltic Pumps

NETZSCH has announced its PERIPRO Peristaltic Pump line. These NETZSCH hose pumps feature a heavy duty construction for demanding applications, with large rollers for longer service life and lower energy consumption. These pumps are ideal for abrasive, corrosive, and viscous fluids. With superior multi-layered hose construction with precision ground diameters, the hoses are a technological leap. Ultimately, these products provide energy savings up to 30% and require 90% less lubricant when compared with shoe technology. pumps-systems.netzsch.com



Sloan ESD-360 Top-Fill Soap Dispenser

Sloan has launched its ESD-360 Top-fill Soap Dispenser to eliminate the hassle of going under the sink deck to refill soap reservoirs. Sloan's top-fill soap dispenser reduces labor time and eliminates safety concerns. Medical-grade connections provide a hygienic environment for soap transfer without drips or spills. The new soap dispenser includes a top cover that slides open via a tamper-resistant unlocking feature. www.sloan.com



Milwaukee Tool SDS Plus Rotary Hammer

Milwaukee Tool delivers an SDS Plus Rotary Hammer with the capability to complete SDS Max applications with the introduction of its new M18 FUEL 1-1/4" SDS Plus D-Handle Rotary Hammer w/ ONE-KEY. Designed to provide professionals with a faster and lighter alternative to compact SDS Max Rotary Hammers, the new D-Handle Rotary Hammer features AUTOSTOP Kickback Control and floor to ceiling dust management. The M18 FUEL 1-1/4" SDS Plus D-Handle Rotary Hammer w/ ONE-KEY delivers 30% faster drilling of 3/4" holes and weighs up to 6 pounds lighter versus SDS Max rotary hammers. Its ergonomic, D-Handle design provides more balance and is optimized for downward drilling. www.milwaukeetool.com



Backflow Direct 4-inch Deringer 20 (DC)

The Backflow Direct 4-inch Deringer 20 (DC) is the shortest, lightest backflow preventer around. Its lay length is just 18.7 inches and it weighs only 42 pounds, making shipping and installation easy and efficient. The valve housing is constructed entirely of 304 stainless steel and the Deringer has two integral shutoff valves with pre-wired supervisory tamper switches. www.BackflowDirect.com