

NOTAS

Para dibujos de línea de productos, [ver hojas de especificaciones específicas del modelo](#).

Toda la información contenida dentro de este documento está sujeta a cambio sin previo aviso.



Imagen para un estándar PWT-ESM RESS se muestra

DESCRIPCIÓN

PWT™ Concealed Solenoid (less sensor) Water Closet PWT Flushometer

CARACTERÍSTICAS

- Program set to 2 activations in 5 minutes with lockout
- Program is field changeable to 15, 30, 45 and 60 minute lockout times, or dorm setting
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Adjustable tailpiece accommodates various installation height
- Single Flush
- Solenoid operated
- Includes touch button
- Stainless steel, vandal proof button, chemical resistant push-button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- Connector cable has white arrows for easy alignment
- Battery powered
- Four (4) Size AA Battery Power source
- Low Battery flashing LED
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Teléfono: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- **Conversion Kit for**
- **Manual flushometers:**
 - Royal 603
 - Royal 611
 - Royal 613
- **Hydraulic flushometers:**
 - Royal 9603
 - Royal 9611
 - Royal 9613
- Fixture Type: Water Closet

DESCARGAS

- [8603-ESM Retrofit Installation Instructions](#)
- [8603-ESM Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Descargas Adicionales](#)