SLOAN.

OPTIONS

Flush Volume

3.5 gpf (13.2 Lpf) (3.5) 1.6 gpf (6.0 Lpf) (1.6) 2.4 gpf (9.1 Lpf) (2.4) 4.5 gpf (17 Lpf) (4.5)

Finish

Polished Chrome (CP) Polished Brass (PB) Brushed Nickel (BN) Brushed Stainless (SF)

Water Efficiency

Water Saver Low Consumption

Handle

Front of Valve (H) Left of Valve (G) Nickel-Silver (YA) Saniguard®

Push Button

3" Metal Oscillating (L3) Metal Index (L) Front of Valve (HL3)

Control Stop

1" Straight (E) Wheel Handle (K) Ground Joint (GJ) Less (L/STOP)

Tailpiece

```
H551A 3 1/16" (H551A-3-1/16)
H551A 4 1/16" (H551A-4-1/16)
H551A 5 1/16" (H551A-5-1/16)
H551A 6 1/16" (H551A-6-1/16)
```

Inlet

Left of Valve (C) Back of Valve (B)

Vacuum Breaker

Less (XYV) V600A

Outlet Tube

Trap Primer (TP)



Image for a standard ROYAL 110 shown

DESCRIPTION

Royal® Exposed Manual Water Closet Flushometer

FEATURES

- Flush volumes start as low as 3.5 gpf/13.2 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID[™] technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Royal Exposed Installation Instructions
- Royal Manual Diaphragm Flushometer Repair and Maintenance Guide
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Additional Downloads



Bumper

Angle Stop Extended (YG) Angle Stop (YO)

Special Features

Whitworth Thread (WWT)

Compliances & Certifications

BAA Compliant BABAA Compliant Made in the USA UPC Certified ADA Compliant cUPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.