

OPTIONS**Flush Volume**

- 0.5 gpf (1.9 Lpf) (0.5)
- 1.0/1.5 gpf (3.8/5.7 Lpf) (1.0/1.5)
- 0.25 gpf (0.9 Lpf) (0.25)
- 1.0 gpf (3.8 Lpf) (1.0)
- 3.5 gpf (13.2 Lpf) (3.5)

Finish

- Polished Chrome (CP)

Power Type

- Battery
- Hardwired

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- High Efficiency

Fixture Type

- Urinal

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical
- Less (L/OR)

Control Stop

- Adjustable Ground Joint for Tek (XDT)
- No (XD)

Special Features

- Fits †Zurn® valve bodies (Z)
- Less Logo (LL)

Specialty

- Retrofit

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- Satisfies LEED Credits
- cUPC Certified



Image for a standard G2 RESS-U shown

DESCRIPTION

G2 Exposed Sensor Urinal Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

BREEAM Water Credit
Green Globes Water Credit
cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.