

OPTIONS**Flush Volume**

- 1.0 gpf (3.8 Lpf) (1.0)
- 3.5 gpf (13.2 Lpf) (3.5)
- 1.5 gpf (5.7 Lpf) (1.5)

Water Efficiency

- Water Saver
- Low Consumption

L Dimension

- 2" - 10 ¾" (51 - 273mm)
- 11" - 12 ¾" (279 - 324mm)
- 13" - 14 ¾" (330 - 375mm)

Control Stop

- Less (L/STOP)

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- UPC Certified
- cUPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ROYAL 990 shown

DESCRIPTION

Royal® Concealed Manual Specialty Urinal Hydraulic Flushometer

FEATURES

- Various types of push-button flush actuators, which can be remotely positioned
- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open actuator, Vandal-resistant stop cap to facilitate security
- Made from rough brass
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Series 900 Flushometers Repair and Maintenance Guide](#)
- [Hydraulic Push Button Options](#)
- [Additional Downloads](#)