

OPTIONS

Flush Volume

1.0 gpf (3.8 Lpf) (1.0)

3.5 gpf (13.2 Lpf) (3.5)

1.5 gpf (5.7 Lpf) (1.5)

Water Efficiency

Water Saver
Low Consumption

L Dimension

2"-10 ¾" (51-273mm) 11"-12 ¾" (279-324mm)

13"-14 3/4" (330-375mm)

Control Stop

Less (L/STOP)

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

UPC Certified

cUPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

 $\mbox{\sc All}$ information contained within this document subject to change without notice.



DESCRIPTION

Royal® Concealed Manual Specialty Urinal Hydraulic Flushometer

FEATURES

- Various types of push-button flush actuators, which can be remotely positioned
- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen actuator, Vandal-resistant stop cap to facilitate security
- Made from rough brass
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Series 900 Flushometers Repair and Maintenance Guide
- Hydraulic Push Button Options
- Additional Downloads