OPTIONS

Flush Volume

- ☐ 0.25 gpf (0.9 Lpf) (0.25)
- ☐ 0.5 gpf (1.9 Lpf) (0.5)
- ☐ 0.125 gpf (0.5 Lpf) (0.125)

Finish

- ☐ Polished Chrome (CP)
- ☐ Brushed Stainless (SF)

Activation

- ☐ Manual

Valve

- ☐ Piston

Water Efficiency

- ☐ High Efficiency

Bypass

- ☐ Filtered

Fixture Type

- ☐ Urinal

Fixture Connection

- ☐ Rear Spud

Installation

- ☐ Concealed

Compliances & Certifications

- ☐ ADA Compliant
- ☐ BREEAM Water Credit
- ☐ EPD
- ☐ Green Globes Water Credit

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



Image for a standard TRF 196 shown

DESCRIPTION

TruFlush Concealed Manual Urinal Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Vandal-resistant wall plate with easy to push button
- Replaceable piston assembly accessible though front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- TruFlush Manual Installation Instructions
- TruFlush Manual Installation Instructions (Spanish)
- TruFlush Manual Maint Guide
- Additional Downloads

VIDEOS

- TruFlush
- TruFlush Installation
- TruFlush Maintenance
- TruFlush Flush Line

Sloan 10500 Seymour Ave, Franklin Park, IL 60131
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com