

OPTIONS

Flush Volume

0.125 gpf (0.5 Lpf) (0.125)

0.25 gpf (0.9 Lpf) (0.25)

0.5 gpf (1.9 Lpf) (0.5)

1.0 gpf (3.8 Lpf) (1.0)

1.5 gpf (5.7 Lpf) (1.5)

Power Type

Battery

Hardwired (HW)

Water Efficiency

High Efficiency

Low Consumption

Water Saver

Bypass

Dual-Filtered Bypass

Override

True Mechanical (TMO)

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

cUPC Certified

UPC Certified

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Royal® Exposed Sensor Urinal Flushometer

FEATURES

- Includes the required wall plate and a purple wall flange to let users know reclaimed water is in use
- All organic rubber has been replaced with synthetic compounds
- Optional purple handle provides additional indication of reclaimed water use
- Critical components, including cover, valve body, control stop and sweat solder kit, are made of semi-red brass
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- EL 600-A Installation Instructions
- EBV 200 Smooth Installation Instructions
- Royal Exposed Installation Instructions
- Royal Exposed Spanish Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- EBV-200-A Repair and Maintenance Guide
- EL600A Smooth Side Mount Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and Maintenance Guide

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



• Additional Downloads