

OPTIONS

Flush Volume

0.125 gpf (0.5 Lpf) (0.125) 0.5 gpf (1.9 Lpf) (0.5) 0.25 gpf (0.9 Lpf) (0.25) 1.0 gpf (3.8 Lpf) (1.0)

Finish

Polished Chrome (CP) Brushed Nickel (BN) Brushed Stainless (SF) Graphite (GR) Polished Brass (PB)

Water Efficiency

High Efficiency Low Consumption

Override

Electrical Less (L/OR)

Control Stop

3/4" 1" Ground Joint (GJ)

Inlet

0.75" 1"

Pipe Support


Solid Ring (YK)

Special Features

Carbon Offset (CO) Less Logo (LL)

Compliances & Certifications

ADA Compliant
BAA Compliant
BABAA Compliant
cUPC Certified
Satisfies LEED Credits
WELL Building Standard
WaterSense Listed
cUPC Green Certified
BREEAM Water Credit
Green Globes Water Credit



DESCRIPTION

ECOS® Exposed Sensor Urinal Flushometer

FEATURES

- Water-efficient flush volume of either .13 gpf or .25 gpf
- Automatically operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions
- Sloan Ecos Valve (Spanish) Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- ECOS Repair and Maintenance Guide
- Sloan Optima Plus Flushometers Repair and Maintenance Guide
- Flushometer Pressure gauges
- Additional Downloads



NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

VIDEOS



PVD Special Finishes