

## OPTIONS

### Flush Volume

- 1.5 gpf (5.7 Lpf) (1.5)
- 1.0 gpf (3.8 Lpf) (1.0)
- 3.5 gpf (13.2 Lpf) (3.5)

### Water Efficiency

- Water Saver
- Low Consumption

### L Dimension

- 10 ¾" (273mm) (10-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 13 ¾" (349mm) (13-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)

### Wall Box

- Standard (not included, order separately)

### Push Button

- 3" Metal Oscillating (L3)
- Metal Index (L)

### Compliances & Certifications

- BAA Compliant
- BABAA Compliant
- Made in the USA
- UPC Certified
- cUPC Certified
- ADA Compliant

## NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



## DESCRIPTION

Royal® Concealed Manual Urinal Flushometer

## FEATURES

- Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which, prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)