OPTIONS

Flush Volume

- ☐ 1.6 gpf (6.0 Lpf) (1.6)
- ☐ 1.28 gpf (4.8 Lpf) (1.28)
- ☐ 1.1 gpf (4.2 Lpf) (1.1)

Power Type

- ☐ Battery
- ☐ Hardwired

Water Efficiency

- ☐ High Efficiency
- ☐ Low Consumption

Override

- ☐ True Mechanical (TMO)

Control Stop

- ☐ 1"

Inlet

- ☐ 1"

Adapter

- ☐ Cast Set Screw Wall Flange (YBC)

Compliances & Certifications

- ☐ ADA Compliant
- ☐ BAA Compliant
- ☐ cUPC Certified
- ☐ UPC Certified
- ☐ BREEAM Water Credit
- ☐ Green Globes Water Credit
- ☐ LEED V4 Water Efficiency Credit
- ☐ Satisfies LEED Credits
- ☐ WaterSense Listed
- ☐ cUPC Green Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



Image for a standard ROYAL 111 SFSM shown

DESCRIPTION

Royal® Exposed Sensor Water Closet Flushometer

FEATURES

- All organic rubber has been replaced with synthetic compounds
- Critical components, including cover, valve body, control stop and sweat solder kit, are made of semi-red brass
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- EBV-500/550-A Installation Instructions
- EL-700/750-A Installation Instructions
- Royal Exposed Installation Instructions
- Royal Exposed Spanish Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and Maintenance Guide
- EBV500/EBV550 Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com