

## OPTIONS

### Flush Volume

- 2.4 gpf (9.1 Lpf) (2.4)
- 4.5 gpf (17 Lpf) (4.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 1.6/3.5 gpf (6.0/13.2 Lpf) (1.6/3.5)
- 3.5 gpf (13.2 Lpf) (3.5)

### Water Efficiency

- Low Consumption
- Water Saver

### Bypass

- Dual-Filtered Fixed Bypass Diaphragm

### Control Stop

- Adjustable Ground Joint for Tek (XDT)
- No (XD)

### Special Features

- Fits †Zurn® valve bodies (Z)

### Compliances & Certifications

- ADA Compliant
- cUPC Certified
- BAA Compliant
- UPC Certified

## NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.



Image for a standard SLOAN RESS-C shown

## DESCRIPTION

Sloan® Exposed Sensor Water Closet Retrofit Flushometer

## FEATURES

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## DOWNLOADS

- [Solis 8100 Series Installation Instructions](#)
- [Solis 8100 Series \(Spanish\) Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)