

OPTIONS**Flush Volume**

- 1.1 gpf (4.2 Lpf) (1.1)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

Finish

- Polished Chrome (CP)
- Brushed Stainless (SF)

Activation

- Manual

Valve

- Piston

Water Efficiency

- High Efficiency
- Low Consumption

Bypass

- Filtered

Fixture Type

- Water Closet

Fixture Connection

- Rear Spud

Installation

- Concealed

Control Stop

- Integrated

Compliances & Certifications

- ADA Compliant
- EPD
- UPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard TRF 156 shown

DESCRIPTION

TruFlush Concealed Manual Water Closet Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Vandal-resistant wall plate with easy to push button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- [TruFlush Manual Installation Instructions](#)
- [TruFlush Manual Installation Instructions \(Spanish\)](#)
- [TruFlush Manual Maint Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ TruFlush
- ▶ TruFlush Installation
- ▶ TruFlush Maintenance
- ▶ TruFlush Flush Line