

**OPTIONS****Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

**Finish**

Polished Chrome (CP)

**Power Type**

Battery

**Activation**

Sensor

**Valve**

Diaphragm

**Water Efficiency**

Water Saver

**Fixture Type**

Water Closet

**Fixture Connection**

Top Spud

**Installation**

Exposed

**Control Stop**

Less (L/STOP)

**Outlet Tube**

Trap Primer (TP)

**Bumper**

Angle Stop (YO)

**Compliances & Certifications**

ADA Compliant

BAA Compliant

BABAA Compliant

UPC Certified

UL Certified

**NOTES**For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard G2 8110 shown

**DESCRIPTION**

G2 Exposed Sensor Water Closet Flushometer

**FEATURES**

- Automatically operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay and Courtesy Flush® override button
- Adjustable tailpiece
- High copper, low zinc brass castings for dezincification resistance
- Available in low consumption (1.6 gpf/6.0 Lpf), water saver (3.5 gpf/13.2 Lpf), and high efficiency (1.28 gpf/4.8 Lpf) models
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [G2 Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)