SLOAN.

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5) 1.28 gpf (4.8 Lpf) (1.28)

Water Efficiency

Low Consumption Water Saver High Efficiency

L Dimension

10 ³⁄₄" (273mm) (10-3/4-LDIM) 8 ³⁄₄" (222mm) (8-3/4-LDIM) 5 ³⁄₄" (146mm) (5-3/4-LDIM) 7 ³⁄₄" (197mm) (7-3/4-LDIM) 12 ³⁄₄" (324mm) (12-3/4-LDIM) 3 ³⁄₄" (95mm) (3-3/4-LDIM) 6 ³⁄₄" (171mm) (6-3/4-LDIM) 11 ³⁄₄" (298mm) (11-3/4-LDIM) 14 ³⁄₄" (375mm) (14-3/4-LDIM) 4 ³⁄₄" (121mm) (4-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Handle

Metal Oscillating (J)

Push Button

3" Metal Oscillating (L3) Less (L/C9A)

Control Stop

1" Straight (E) Less (L/STOP) Ground Joint (GJ)

Vacuum Breaker

Less (XYV)

Outlet Tube

Trap Primer (TP)

Compliances & Certifications

BAA Compliant BABAA Compliant Made in the USA UPC Certified cUPC Certified WaterSense Listed



Image for a standard ROYAL 611 shown

DESCRIPTION

Royal® Concealed Manual Water Closet Flushometer

FEATURES

- Royal® and Regal® Prison Flushometers feature all the performance benefits of standard concealed, diaphragm model Flushometers with added durability to withstand rough environments
- Various flush volumes available to match with existing fixtures and meet water-efficiency goals
- Choose from Flushometers intended for use with stainlesssteel water closet fixtures from Acorn®, Metcraft® and other manufacturers
- Diaphragm, handle packing, stop seat and vacuum breaker molded from PERMEX® rubber compound for chloramine resistance
- Vandal-proof, push-button operation designed with non-holdopen feature to keep fixture from surpassing intended water consumption
- Adjustable tailpiece accommodates various installation heights
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Concealed Flushometer Installation Instructions for Stainless Steel Fixtures
- Control Stop Repair and Maintenance Guide

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



BREEAM Water Credit Green Globes Water Credit LEED V4 Water Efficiency Credit Satisfies LEED Credits

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Additional Downloads