

OPTIONS**Flush Volume**

1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)
1.28 gpf (4.8 Lpf) (1.28)
1.28/1.1 gpf (4.8/4.2 Lpf) (1.28/1.1)

Finish

Polished Chrome (CP)
Brushed Stainless (SF)

Power Type

Battery
Hardwired

Activation

Sensor

Valve

Diaphragm

Water Efficiency

High Efficiency

Bypass

Dual-Filtered Bypass

Fixture Type

Water Closet

Fixture Connection

Top Spud

Installation

Exposed

Override

Electrical

Handle

Less Handle Body (LH)

Control Stop

No (XD)

Special Features

Fits †Zurn® valve bodies (Z)

Specialty

Retrofit

Compliances & Certifications

BREEAM Water Credit
cUPC Green Certified
ADA Compliant



Image for a standard ECOS RESS-C shown

DESCRIPTION

ECOS® Exposed Sensor Water Closet Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [Sloan ECOS Valve Installation Instructions](#)
- [ECOS Single Flush HW Flushometer and Retrofit](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [ECOS HW Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Green Globes Water Credit
cUPC Certified
BAA Compliant
Carbon Neutral
EPD
HPD
Satisfies LEED Credits

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.