

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5)

Finish

Polished Chrome (CP)

Activation

Manual

Valve

Diaphragm

Water Efficiency

Water Saver Low Consumption

Fixture Type

Water Closet

Fixture Connection

Top Spud

Installation

Exposed

Push Button

3" Metal Oscillating (L3) Metal Index (L)

Control Stop

No (XD)

Adjustable Ground Joint for Tek (XDT)

Vacuum Breaker

Less (XYV)

Outlet Tube

Trap Primer (TP)

Bumper

Angle Stop Extended (YG)

Compliances & Certifications

BAA Compliant

BABAA Compliant

Made in the USA

UPC Certified

ADA Compliant

cUPC Certified



DESCRIPTION

Royal® Exposed Manual Water Closet Flushometer

FEATURES

- Various water-saving flush volumes for urinals and water closets
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents fixture from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Vandal-resistant stop cap prevents tampering
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Royal Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and Maintenance Guide
- Additional Downloads

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.