

OPTIONS

Flush Volume

- 0.5 gpf (1.9 Lpf) (0.5)
- 1.0/1.5 gpf (3.8/5.7 Lpf) (1.0/1.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 0.125 gpf (0.5 Lpf) (0.125)

Water Efficiency

- High Efficiency
- Low Consumption

Bypass

- Dual-Filtered Fixed Bypass Diaphragm

Control Stop

- Adjustable Ground Joint for Tek (XDT)
- No (XD)

Special Features

- Fits †Zurn® valve bodies (Z)

Compliances & Certifications

- ADA Compliant
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- Satisfies LEED Credits
- cUPC Green Certified
- BAA Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.



Image for a standard SLOAN RESS-U shown

DESCRIPTION

Sloan® Exposed Sensor Urinal Retrofit Flushometer

FEATURES

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Optima Plus Valve \(SP\) Installation Instructions](#)
- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)