

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 1.28 gpf (4.8 Lpf) (1.28)

Finish

Polished Chrome (CP) Brushed Stainless (SF) Brushed Nickel (BN) Graphite (GR) Polished Brass (PB)

Power Type

Battery

Activation

Sensor

Valve

Diaphragm

Water Efficiency

Low Consumption High Efficiency

Fixture Type

Water Closet

Fixture Connection

Top Spud

Installation

Exposed

Handle

Less Handle Body (LH)

Control Stop

Less (L/STOP)

Vacuum Breaker

Less (XYV)

Outlet Tube

Trap Primer (TP)

Bumper

Angle Stop (YO)

Pipe Support

Solid Ring (YK)

Special Features

Less Logo (LL)



DESCRIPTION

G2 Exposed Sensor Water Closet Flushometer

FEATURES

- Automatically operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay and Courtesy Flush® override button
- Adjustable tailpiece
- High copper, low zinc brass castings for dezincification resistance
- Available in low consumption (1.6 gpf/6.0 Lpf), water saver (3.5 gpf/13.2 Lpf), and high efficiency (1.28 gpf/4.8 Lpf) models
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- G2 and ECOS Single Flush Optima Plus Valve Installation Instructions
- G2 Repair and Maintenance Guide
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Sloan Optima Plus Flushometers Repair and Maintenance Guide
- Additional Downloads



Carbon Offset (CO)

WaterSense Listed cUPC Green Certified

Compliances & Certifications

ADA Compliant
BAA Compliant
BABAA Compliant
cUPC Certified
Satisfies LEED Credits
BREEAM Water Credit
Green Globes Water Credit
LEED V4 Water Efficiency Credit

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

VIDEOS



PVD Special Finishes