

OPTIONS

Power Type

Solar

Body Type

Mid

Mounting

Deck

Power Supply

Solar (SOL)

Sensor Type

Infrared

Flow Rate

0.35 gpm (1.3 Lpm) (0.35GPM) 0.5 gpm (1.9 Lpm) (0.5GPM) 1.0 gpm (3.8 Lpm) (1.0GPM)

Spray Type

Multi-Laminar (MLM) Aerated (AER) Laminar (LAM)

Finish

Polished Chrome (CP) Brushed Stainless (SF) Polished Brass (PB) Brushed Nickel (BN)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)
Mixer Not Included
Integrated Thermostatic Mixer (ITM)

Special Features

IQ Click (IQ)
2" Extension (EXT)
Carbon Offset (CO)
Less Logo (LL)

Compliances & Certifications

ADA Compliant
ASME A112.18.1 Compliant
CEC Compliant
EPD
HPD



DESCRIPTION

Optima® Solar-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature
- Automatic Self-adapting Sensor Technology
- Solar Powered
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- Appropriate Mounting Hardware included
- Includes 6 VDC Lithium Battery Back-up Power Source
- 3 year limited warranty

DOWNLOADS

- EAF 200/225/250/275 Installation Instructions
- EAF 200/225/250/275 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 275 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads

VIDEOS



PVD Special Finishes



NSF-61 NYC604.4 Proposition 65 TAS UPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.