SLOAN.

OPTIONS

Flush Volume

0.5 gpf (1.9 Lpf) (0.5) 0.125 gpf (0.5 Lpf) (0.125) 0.25 gpf (0.9 Lpf) (0.25) 1.0 gpf (3.8 Lpf) (1.0)

Water Efficiency

High Efficiency Low Consumption

Control Stop

3/4" Ground Joint (GJ)

Adapter

Cast Set Screw Wall Flange & Casing Tube (YBYC)

Compliances & Certifications

BAA Compliant

BABAA Compliant

Made in the USA

cUPC Certified

- ADA Compliant
- BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



Image for a standard CROWN 186 shown

DESCRIPTION

Crown® Exposed Manual Urinal Flushometer

FEATURES

- Flush volumes to meet water-efficiency goals
- Unique cover design isolates threads from water source, protecting threads from harsh water conditions
- Fixed volume piston with filtered O-ring bypass
- ADA-compliant, metal oscillating, non-hold open handle with triple seal handle packing keeps fixture from exceeding intended flush volume
- Locking, vandal-resistant stop cap prevents tampering
- Adjustable tailpiece accommodates different widths
- High copper, low zinc brass casting for dezincification resistance ensures long life
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Crown Piston Type Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Crown/Crown II Repair and Maintenance Guide
- Crown Piston Assembly Repair Kit
- Flushometer Pressure gauges
- Additional Downloads



VIDEOS

Crown Piston Flushometer Basics

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com