

OPTIONS

Power Type

Hardwired

Body Type

Gooseneck

Mounting

Deck

Power Supply

Plug Adapter (PLG)

Sensor Type

Infrared (IR)

Flow Rate

- 1.0 gpm (4 Lpm) (1.0GPM)
- 1.5 gpm (6 Lpm) (1.5GPM)
- 2.2 gpm (8 Lpm) (2.2GPM)
- 0.35 gpm (1 Lpm) (0.35GPM)
- 0.5 gpm (2 Lpm) (0.5GPM)

Spray Type

- Laminar (LAM)
- Multi-Laminar (MLM)

Trim Plate

4" (102mm) (4)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

- Back-Check Tee (TEE)
- Below Deck Manual Mixing Valve (BDM)

Special Features

Battery Backup

Compliances & Certifications

- ADA Compliant
- ASME A112.18.1 Compliant
- Proposition 65
- TAS
- UPC Certified
- UPC Low Lead Compliant
- cUPC Certified
- cUPC Low Lead Compliant



Image for a standard SF-2200 shown

DESCRIPTION

Sloan® Hardwired-Powered Deck-Mounted Gooseneck Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Gooseneck Hand Washing Faucet with the following features:

- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

DOWNLOADS

- [SF Series Installation Instructions](#)
- [SF Series \(FR\) Installation Instructions](#)
- [SF Series \(SP\) Installation Instructions](#)
- [SFP 35-A Installation Instructions](#)
- [Trim Plate Guide](#)
- [Sloan 2100/2150 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

CEC Compliant
NYC604.4

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.