

OPTIONS

Power Type

Hardwired

Body Type

Gooseneck

Mounting

Deck

Power Supply

Hardwired Less Transformer (HLT)

Plug Adapter (PLG)

Box Transformer (BOX)

Sensor Type

Infrared

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM)

1.0 gpm (3.8 Lpm) (1.0GPM)

0.5 gpm (1.9 Lpm) (0.5GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

Spray Type

Laminar (LAM)

Multi-Laminar (MLM)

Finish

Brushed Nickel (BN)

Brushed Stainless (SF)

Polished Brass (PB)

Polished Chrome (CP)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Mixer Not Included

Special Features

IQ Click (IQ)

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

EPD

HPD

Proposition 65

TAS



DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Gooseneck Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Gooseneck Hand Washing Faucet with the following features:

- 12/24 hour Hygienic Rinse Line Purge Function Field Settable
- Unitary Spout Housing Assembly for Easy Cleaning
- Modular One-piece Construction with all Concealed Components above deck
- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Bi-stable Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 123 VAC/6.75 VDC Plug-in Adapter (must be ordered separately for Less Adapter (-LT) faucets)
- IQ-Click feature permits activation of continuous run and temporary off modes
- Appropriate Mounting Hardware included
- 3 year limited warranty

DOWNLOADS

- EAF 700/750 Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 700 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads



UPC Certified UPC Low Lead Compliant WELL Building Standard

VIDEOS



NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.