# SLOAN.

## OPTIONS

#### **Power Type**

Battery

#### **Body Type**

Mid

## Mounting

Deck

# **Power Supply**

Battery (BAT)

## Sensor Type

Infrared

## Flow Rate

0.35 gpm (1.3 Lpm) (0.35GPM) 0.5 gpm (1.9 Lpm) (0.5GPM) 1.5 gpm (5.7 Lpm) (1.5GPM)

## Spray Type

Multi-Laminar (MLM) Aerated (AER)

## Finish

Polished Chrome (CP) Brushed Nickel (BN) Brushed Stainless (SF) Graphite (GR) Polished Brass (PB)

# **Control Access**

Above Deck

## Mixer

Integrated Side Mixer (ISM) Mixer Not Included

## **Special Features**

IQ Click (IQ)

# **Compliances & Certifications**

ADA Compliant ASME A112.18.1 Compliant CEC Compliant EPD HPD NSF-61 Proposition 65 Satisfies LEED Credits TAS



Image for a standard EAF-350 shown

# DESCRIPTION

Optima® Battery-Powered Deck-Mounted Mid Body Faucet

## FEATURES


Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensor with Automatic Setting Feature and Microprocessor
- Bi-Stable Magnetic Solenoid Valve (for increased energy savings)
- Adjustable Hot Water Limit Set (with ISM Mixer)
- Water Supply Connection with Flexible High-Pressure Hose and Strainer
- 6V Lithium CR-P2 Commercial Battery included
- IR-Click feature permits activation of continuous run and temporary off modes
- Appropriate Mounting Hardware included
- 3 year limited warranty

## DOWNLOADS

- EAF 3X0 Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 3X0 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads

## VIDEOS



Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



UPC Certified

# NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.