

OPTIONS

Power Type

Battery

Turbine

Body Type

Mid

Mounting

Deck

Power Supply

Battery (BAT)

Battery + Turbine (TUR)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM)

Laminar (LAM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)

Above Deck Mixer (ADM)

Below Deck Manual Mixing Valve (BDM)

Below Deck Thermostatic Mixing Valve (BDT)

Special Features

Less Logo (LL)

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

EPD

HPD



DESCRIPTION

Optima® Battery or Turbine-Powered Deck-Mounted Mid Body Faucet

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings AdjustmentOn-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- Optima Smart Faucet Below Deck Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- ETF-80/880 and EBF-85/187 Below Deck Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads



IAPMO

NSF-61

Proposition 65

TAS

UPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

VIDEOS





Sloan Optima Below Deck Faucet