

**OPTIONS****Power Type**

Battery

**Body Type**

Mid

**Mounting**

Deck

**Power Supply**

Battery (BAT)

**Sensor Type**

Infrared (IR)

**Flow Rate**

0.5 gpm (2 Lpm) (0.5GPM)

0.35 gpm (1 Lpm) (0.35GPM)

**Spray Type**

Multi-Laminar (MLM)

**Spout Type**

Pedestal

**Trim Plate**

4" (102mm) (4)

**Finish**

Polished Chrome (CP)

**Control Access**

Below Deck

**Mixer**

Back-Check Tee (TEE)

Below Deck Manual Mixing Valve (BDM)

**Compliances & Certifications**

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

CalGreen Compliant

NYC604.4


Proposition 65

TAS

UPC Certified

UPC Low Lead Compliant

cUPC Certified

**NOTES**For product line drawings, [view model-specific spec sheets](#).**DESCRIPTION**

Sloan® Battery-Powered Deck-Mounted Mid Body Faucet

**FEATURES**

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Pedestal Hand Washing Faucet with the following features:

- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

**DOWNLOADS**

- [SF Series Installation Instructions](#)
- [SF Series \(FR\) Installation Instructions](#)
- [SF Series \(SP\) Installation Instructions](#)
- [SFP 35-A Installation Instructions](#)
- [Trim Plate Guide](#)
- [Sloan 2400/2450 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

**Sloan 10500 Seymour Ave, Franklin Park, IL 60131**

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)