SLOAN.

OPTIONS

Power Type

Battery

Body Type

Gooseneck

Mounting

Deck

Power Supply

Battery (BAT)

Sensor Type

Infrared

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM) 0.5 gpm (1.9 Lpm) (0.5GPM) 1.0 gpm (3.8 Lpm) (1.0GPM) 0.35 gpm (1.3 Lpm) (0.35GPM)

Spray Type

Laminar (LAM) Multi-Laminar (MLM)

Finish

Brushed Nickel (BN) Brushed Stainless (SF) Polished Brass (PB) Polished Chrome (CP)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM) Mixer Not Included

Special Features

IQ Click (IQ)

Compliances & Certifications

ADA Compliant ASME A112.18.1 Compliant CEC Compliant EPD HPD Proposition 65 TAS UPC Certified UPC Low Lead Compliant



Image for a standard EAF-750 shown

DESCRIPTION

Optima® Battery-Powered Deck-Mounted Gooseneck Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Gooseneck Hand Washing Faucet with the following features:

- 12/24 Hour Hygienic Rinse Line Purge Function Field Settable
- Unitary Spout Housing Assembly for Easy Cleaning
- Modular One-piece Construction with all Concealed Components above deck
- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Low Battery Indicator
- Bi-stable Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 8 volt Lithium CR P2 Commercial Battery included
- Appropriate Mounting Hardware included
- IQ-Click feature permits activation of continuous run and temporary off modes
- Installation Similar to Conventional Single Lever Faucet
- 3 year limited warranty

DOWNLOADS

- EAF 700/750 Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 750 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads



WELL Building Standard

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.