

# OPTIONS

## Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM) 1.5 gpm (5.7 Lpm) (1.5GPM)

# Spray Type

Multi-Laminar (MLM) Aerated (installed) or Laminar (in box)

## **Trim Plate**

None 8" (203mm) (8)

#### Mixer

Back-Check Tee (TEE) Integrated Side Mixer (ISM)

#### NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



Image for a standard EFX-377 shown

## DESCRIPTION

BASYS® Solar-Powered Deck-Mounted Low Body Guided Handwashing Display

## FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hose, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation (pedestal)
- Includes all mounting hardware
- 3 year limited warranty

#### DOWNLOADS

- EFX 3Xx/6Xx Active IR Installation Instructions
- EFX 3Xx/6Xx Active IR (SP) Installation Instructions
- Trim Plate Guide

- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-3XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads

## VIDEOS

- BASYS® Guided Handwashing Faucets
- BASYS® Faucet Installation and Features
- BASYS® Faucet Installation Low Height Model
  - Sloan Connect App®

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com