

OPTIONS

Power Type

Hardwired

Body Type

Low

Mounting

Deck

Power Supply

Hardwired Less Transformer (HLT)

Plug Adapter (PLG)

Box Transformer (BOX)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

Spray Type

Multi-Laminar (MLM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

None

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Above Deck Mixer (ADM)

Back-Check Tee (TEE)

Below Deck Manual Mixing Valve (BDM)

Below Deck Thermostatic Mixing Valve (BDT)

Wash Station

Yes (WS)

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

CalGreen Compliant

EPD

GPC 0.25 or less

HPD



DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Low Body Faucet

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- Optima Smart Faucet Below Deck Installation Instructions
- Trim Plate Guide
- Faucet Spray Heads Repair and Maintenance Guide
- ETF-660/EBF-665 Below Deck Repair and Maintenance Guide
- Additional Downloads

VIDEOS



IAPMO

NSF-61

NYC604.4

Sloan Connect App®

Sloan Optima Below Deck Faucet

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.