

OPTIONS**Power Supply**

- Plug Adapter (PLG)
- Hardwired Less Plug (HLP)
- Box Transformer (BOX)

Flow Rate

- 1.5 gpm (6 Lpm) (1.5GPM)
- 0.5 gpm (2 Lpm) (0.5GPM)

Spray Type

- Aerated (installed) or Laminar (in box)
- Multi-Laminar (MLM)

Mixer

- Mixer Not Included
- Below Deck Manual Mixing Valve (BDM)
- Below Deck Thermostatic Mixing Valve (BDT)

Special Features

- Lithium Batteries

Compliances & Certifications

- ADA Compliant
- ASME A112.18.1 Compliant
- CEC Compliant
- Proposition 65
- TAS
- UPC Certified
- UPC Low Lead Compliant
- cUPC Certified
- cUPC Low Lead Compliant
- CalGreen Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.



Image for a standard EFX-800 shown

DESCRIPTION

BASYS® Hardwired-Powered Wall-Mounted Wall Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components are stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral above deck water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-73
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Bi-stable magnetic solenoid
- One (1) CR-P2 battery
- Double infrared sensors with automatic setting feature
- Optional Wall Flange included
- Line Purge mode, eliminates stagnant water
- Adjustable time-outs and sleep/cleaning mode
- Sleep/cleaning Mode
- Includes all mounting hardware
- 3 year limited warranty

DOWNLOADS


- [EFX 8Xx Installation Instructions](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](#)

- [EFX 8Xx \(SP\) Installation Instructions](#)
- [EFX 1009-A/1010-A/1018-A Installation Instructions](#)
- [Trim Plates Repair and Maintenance Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [EFX-8XX Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [BASYS[®] Faucet Installation and Features](#)