

OPTIONS**Power Type**

Battery
Turbine

Body Type

Low Integrated Base

Mounting

Deck

Power Supply

Battery (BAT)
Battery + Turbine (TUR)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)
0.35 gpm (1.3 Lpm) (0.35GPM)
2.2 gpm (8.3 Lpm) (2.2GPM)

Spray Type

Multi-Laminar (MLM)
Aerated (AER)

Trim Plate

None
8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)
Below Deck Manual Mixing Valve (BDM)
Below Deck Thermostatic Mixing Valve (BDT)

Special Features

Less Logo (LL)
Line Flush (LF)

Compliances & Certifications

ADA Compliant
ASME A112.18.1 Compliant
EPD
HPD
IAPMO



Image for a standard EBF-650 shown

DESCRIPTION

Optima® Battery or Turbine-Powered Deck-Mounted Low Integrated Base Body Faucet

FEATURES

Commercial Grade Faucet, ADA Compliant, Cast Brass Spout, Quick Connect Fittings, Integrated Water Shut-off, Wireless Settings Adjustment, On-demand or Metered activation, Hygienic Line Flush, Water Usage and Battery Strength Reporting, Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Graphite

DOWNLOADS

- [Optima Smart Faucet Below Deck Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [ETF-600/EBF-650 Below Deck Repair and Maintenance Guide](#)
- [Trim Plate Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [Sloan Connect App®](#)
- ▶ [Sloan Optima Below Deck Faucet](#)
- ▶ [PVD Special Finishes](#)

NSF-61
Proposition 65
TAS
UPC Certified
UPC Low Lead Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.