

OPTIONS

Power Supply

Battery (BAT) Battery + Turbine (TUR)

Flow Rate

2.2 gpm (8.3 Lpm) (2.2GPM)
0.35 gpm (1.3 Lpm) (0.35GPM)
0.5 gpm (1.9 Lpm) (0.5GPM)
1.0 gpm (3.8 Lpm) (1.0GPM)
1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Laminar (LAM) Multi-Laminar (MLM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

Mixer

Back-Check Tee (TEE) Above Deck Mixer (ADM) Below Deck Thermostatic Mixing Valve (BDT) Below Deck Manual Mixing Valve (BDM)

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



Image for a standard EBF-775 shown

DESCRIPTION

Optima® Battery or Turbine-Powered Deck-Mounted Gooseneck Body Faucet

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- Optima Smart Faucet Below Deck Installation Instructions
- ETF-770/EBF-775 Below Deck Repair and Maintenance Guide
- Trim Plate Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads



VIDEOS

Sloan Connect App®

Sloan Optima Below Deck Faucet