

**OPTIONS****Flush Volume**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

**Water Efficiency**

Low Consumption

**Compliances & Certifications**

ADA Compliant

BAA Compliant

BABAA Compliant

EPD

Satisfies LEED Credits

cUPC Certified

cUPC Green Certified

WaterSense Listed

**NOTES**For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard Royal II 111 shown

**DESCRIPTION**

Royal® Exposed Manual Water Closet Flushometer

**FEATURES**

- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Aesthetically contoured Cover, Handle Socket and Flanges
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [Royal Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal II Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)