

OPTIONS**Flush Volume**

- 0.125 gpf (0.5 Lpf) (0.125)
- 0.25 gpf (0.9 Lpf) (0.25)
- 0.5 gpf (1.9 Lpf) (0.5)

Finish

- Brushed Nickel (BN)
- Brushed Stainless (SF)
- Graphite (GR)
- Polished Brass (PB)
- Polished Chrome (CP)

Compliances & Certifications

- BAA Compliant
- ADA Compliant
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- HPD
- LEED Materials & Resources HPD Credit
- cUPC Green Certified
- cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard CX 198 shown

DESCRIPTION

CX Concealed Manual Urinal Flushometer

FEATURES

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- ADA compliant push button
- Vandal resistant wall plate
- Adjustable flush connection
- 8 1/2"(W) x 9 1/4"(H) Wall Box Panel Dimension

DOWNLOADS

- [CX 158/198 Installation Instructions](#)
- [CX 158/198 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [CX Flushometer Product Video](#)
- ▶ [CX Flushometer - Manual Installation](#)
- ▶ [CX Flushometer - Manual Vacuum Service](#)
- ▶ [CX Flushometer - Manual Piston Service](#)
- ▶ [CX Flushometer Product Video \(Spanish\)](#)
- ▶ [PVD Special Finishes](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com