

**OPTIONS****Flush Volume**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

**Wall Plate Finish**

Black (BLK)

Brushed Nickel (BN)

Brushed Stainless (SF)

Polished Brass (PB)

Polished Chrome (CP)

**Compliances & Certifications**

ADA Compliant

BAA Compliant

cUPC Certified

BREEAM Water Credit

Green Globes Water Credit

cUPC Green Certified

WaterSense Listed

**NOTES**For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard CX 8158 shown

**DESCRIPTION**

CX Concealed Sensor Water Closet Flushometer

**FEATURES**

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- Sensor activated, hands-free operation
- Battery operated with hardwired option
- Electronic override button
- Low battery indicator light
- Vandal resistant wall plate
- Adjustable flush connection

**DOWNLOADS**

- [CX 8158 / 8198 Installation Instructions](#)
- [CX 8158 / 8198 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

**VIDEOS**

- ▶ [CX Flushometer Product Video](#)
- ▶ [CX Flushometer - Sensor Installation](#)
- ▶ [CX Flushometer - Sensor Vacuum Service](#)
- ▶ [CX Flushometer - Sensor Piston Service](#)
- ▶ [CX Flushometer Product Video \(Spanish\)](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)