

OPTIONS

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM) 0.5 gpm (1.9 Lpm) (0.5GPM)

Spray Type

Multi-Laminar (MLM)
Aerated (installed) or Laminar (in box)

Trim Plate

None

4" (102mm) (4) 8" (203mm) (8)

Mixer

Integrated Side Mixer (ISM)
Back-Check Tee (TEE)

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



DESCRIPTION

BASYS® Solar-Powered Deck-Mounted Mid Body Guided Handwashing Display

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- · Includes all mounting hardware
- · Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty



DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx (SP) Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- Additional Downloads

VIDEOS

- BASYS® Guided Handwashing Faucets
- BASYS® Faucet Installation and Features
- BASYS® Faucet Installation Mid Height Model
- Sloan Connect App®