

OPTIONS

Power Type

Battery

Body Type

Mid

Mounting

Deck

Power Supply

Battery (BAT)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM)

Aerated (installed) or Laminar (in box)

Laminar (LAM)

Trim Plate

None

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Brushed Nickel (BN)

Brushed Stainless (SF)

Graphite (GR)

Polished Brass (PB)

None

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Back-Check Tee (TEE)

Below Deck Thermostatic Mixing Valve (BDT)

Below Deck Manual Mixing Valve (BDM)

Mixer Not Included

Special Features

Drain Pop Up (DPU)

Carbon Offset (CO)



Image for a standard EFX-250 shown

DESCRIPTION

BASYS® Battery-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Compliances & Certifications

ADA Compliant
CEC Compliant
EPD
HPD
Proposition 65
WELL Building Standard
cUPC Low Lead Compliant
cUPC Certified
ASME A112.18.1 Compliant
UPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

DOWNLOADS

- [EFX 1Xx/2Xx Installation Instructions](#)
- [EFX 1Xx/2Xx Caddy Replacement Installation Instructions](#)
- [Trim Plate Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [EFX-2XX Repair and Maintenance Guide](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [BASYS® Faucet Installation and Features](#)
- ▶ [BASYS® Faucet Installation Mid Height Model](#)
- ▶ [PVD Special Finishes](#)
- ▶ [Sloan Connect App®](#)