OPTIONS

Power Type

- ☐ Battery

Body Type

- ☐ Mid

Mounting

- ☐ Deck

Power Supply

- ☐ Battery (BAT)

Sensor Type

- ☐ Infrared

Flow Rate

- ☐ 0.5 gpm (1.9 Lpm) (0.5GPM)
- ☐ 1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

- ☐ Multi-Laminar (MLM)
- ☐ Aerated (installed) or Laminar (in box)
- ☐ Laminar (LAM)

Trim Plate

- ☐ None
- ☐ 4" (102mm) (4)
- ☐ 8" (203mm) (8)

Finish

- ☐ Polished Chrome (CP)
- ☐ Brushed Nickel (BN)
- ☐ Brushed Stainless (SF)
- ☐ Graphite (GR)
- ☐ Polished Brass (PB)

Control Access

- ☐ Above Deck

Mixer

- ☐ Integrated Side Mixer (ISM)
- ☐ Back-Check Tee (TEE)
- ☐ Below Deck Thermostatic Mixing Valve (BDT)
- ☐ Below Deck Manual Mixing Valve (BDM)
- ☐ Mixer Not Included

Special Features

- ☐ Drain Pop Up (DPU)
- ☐ Carbon Offset (CO)

Compliances & Certifications

Image for a standard EFX-250 shown

DESCRIPTION

BASYS® Battery-Powered Deck-Mounted Mid Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8” compression connections
- Bi-stable magnetic solenoid
- Four (4) “AA” alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty

Sloan 10500 Seymour Ave, Franklin Park, IL 60131
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Downloaded 04/20/24 • Revised 03/20/24 • View Latest Version

- ☐ ADA Compliant
- ☐ CEC Compliant
- ☐ EPD
- ☐ HPD
- ☐ IAPMO
- ☐ Proposition 65
- ☐ WELL Building Standard
- ☐ WaterSense Listed
- ☐ cUPC Certified
- ☐ cUPC Low Lead Compliant

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet.
Find a compatible sink for this faucet.

DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- Additional Downloads

VIDEOS

- BASYS® Faucet Installation and Features
- BASYS® Faucet Installation Mid Height Model
- PVD Special Finishes
- Sloan Connect App®

Sloan 10500 Seymour Ave, Franklin Park, IL 60131
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Downloaded 04/20/24 • Revised 03/20/24 • View Latest Version