

OPTIONS

Power Type

Hardwired

Body Type

Mid

Mounting

Deck

Power Supply

Plug Adapter (PLG)

Hardwired Less Transformer (HLT)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM) 0.35 gpm (1.3 Lpm) (0.35GPM) 1.0 gpm (3.8 Lpm) (1.0GPM)

Spray Type

Multi-Laminar (MLM)

Aerated (AER)

Laminar (LAM)

Finish

Polished Chrome (CP)

Polished Brass (PB)

Brushed Stainless (SF)

Brushed Nickel (BN)

Graphite (GR)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Mixer Not Included

Integrated Thermostatic Mixer (ITM)

Special Features

IO Click (IO)

Carbon Offset (CO)

IC Click (IC)

Drain Pop Up (DPU)

Compliances & Certifications

ADA Compliant ASME A112.18.1 Compliant CEC Compliant



DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Automatic Self-adapting Sensor Technology
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 Volt DC Plug-in Adapter (must be ordered separately for Less Adapter/Transformer (-LT) faucets)
- Appropriate Mounting Hardware included
- 3 year limited warranty

DOWNLOADS

- EAF 200/225/250/275 Installation Instructions
- EAF 200/225/250/275 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 200 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads

VIDEOS



Sloan Connect App®

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



EPD

HPD

NSF-61

NYC604.4

Proposition 65

TAS

UPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.