# SLOAN.

# OPTIONS

#### **Flush Volume**

1.6 gpf (6.0 Lpf) (1.6) 1.28 gpf (4.8 Lpf) (1.28) 1.1 gpf (4.2 Lpf) (1.1) 2.4 gpf (9.1 Lpf) (2.4)

# Finish

Polished Chrome (CP) Graphite (GR) Brushed Nickel (BN) Brushed Stainless (SF) Polished Brass (PB)

## **Power Type**

Hardwired (HW)

#### Activation

Sensor

#### Valve

Diaphragm

#### Water Efficiency

Low Consumption High Efficiency Water Saver

## **Fixture Type**

Water Closet

## **Fixture Connection**

Top Spud

#### Installation

Exposed

## Override

Electrical True Mechanical (TMO)

## **Control Stop**

1" Less (L/STOP)

## Vacuum Breaker

Less (XYV)

## Offset

2" (51mm) (2-OFST)

## **Outlet Tube**

Trap Primer (TP)

# ROYAL® SENSOR FLUSHOMETER ROYAL 111 ESS





Image for a standard ROYAL 111 ESS shown

# DESCRIPTION

Royal® Exposed Sensor Hardwired Water Closet Flushometer

#### FEATURES

- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID<sup>™</sup> technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## DOWNLOADS

- Royal ESS 110/111 Electrical Box Installation Instructions
- Royal ESS Concealed and Exposed Installation Instructions
- Royal ESS TMO Installation Instructions
- Royal 110/111/180/186 ESS TMO (Spanish) Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Optima ESS Repair and Maintenance Guide

# SLOAN.

# Voltage

24V

#### Adapter

28mm Sweat Solder Adapter Kit Cast Set Screw Wall Flange (YBC)

#### Bumper

Angle Stop (YO) Angle Stop Extended (YG)

# **Compliances & Certifications**

ADA Compliant BAA Compliant BABAA Compliant UL Certified cUPC Certified Satisfies LEED Credits WaterSense Listed cUPC Green Certified BREEAM Water Credit Green Globes Water Credit

# NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

- Optima ESS TMO Exposed Repair and Maintenance Guide
- Additional Downloads

# VIDEOS

- ESS Flushometer
- PVD Special Finishes