

# PWT<sup>™</sup> SOLENOID (LESS SENSOR) FLUSHOMETER PWT-ESM RESS

## OPTIONS

#### **Flush Volume**

1.28 gpf (4.8 Lpf) (1.28) 1.6/2.4/3.5 gpf (6.0/9.1/13.2 Lpf) (1.6/2.4/3.5)

#### **Push Button**

Metal Button Fixture Wall Actuator (MBFW)

#### **Compliances & Certifications**

ADA Compliant BAA Compliant UL Certified UPC Certified cUPC Certified WaterSense Listed

#### NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



Image for a standard PWT-ESM RESS shown

### DESCRIPTION

 $\mathsf{PWT}^{\mbox{\tiny TM}}$  Concealed Solenoid (less sensor) Water Closet  $\mathsf{PWT}$  Flushometer

#### FEATURES

- Program set to 2 activations in 5 minutes with lockout
- Program is field changeable to 15, 30, 45 and 60 minute lockout times, or dorm setting
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Adjustable tailpiece accommodates various installation height
- Single Flush
- Solenoid operated
- Includes touch button
- Stainless steel, vandal proof button, chemical resistant pushbutton operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- Connector cable has white arrows for easy alignment
- Battery powered
- Four (4) Size AA Battery Power source
- Low Battery flashing LED
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



- Conversion Kit for
- Manual flushometers:
- Royal 603
- Royal 611
- Royal 613
- Hydraulic flushometers:
- Royal 9603
- Royal 9611
- Royal 9613
- Fixture Type: Water Closet

## DOWNLOADS

- 8603-ESM Retrofit Installation Instructions
- 8603-ESM Maintenance Guide
- Control Stop Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com