



Sloan Hybrid Urinal - HYB 1000 Sloan Valve

Final Assembly: Zhangzhou, China

Life Expectancy: 25 Years

End of Life Options: Salvageable/Reusable in its Entirety, Recyclable (97%), Landfill (3%)

Ingredients:

Body: Porcelain, Glaze; **Cartridge:** ABS Plastic, 2-Octyldodecanol; **Cartridge Housing:** Stainless Steel, Polypropylene; **Waterfree Wall Plaque:** Stainless Steel; **Mounting Hardware:** Stainless Steel; **Drain Line Support:** Galvanized Steel, Plating Zinc; **Nut/Slip Joint:** ABS Plastic; **Rubber Flange Seal;** Clear Inspection Disk: PETE; **Hose Clamp:** Zinc; **Insert Tube:** Polypropylene; **Hanger Bracket:** Stainless Steel; **Stamped Retainer Flange:** Galvanized Steel, Zinc; **Hybrid Air Gap:** EPDM, ABS Plastic, Tonval Brass, Stainless Steel, Polypropylene; **Base Plate Assembly:** Tonval Brass, EPDM, ABS Plastic, Stainless Steel, Thermoplastic Elastomers, Polyphthalamide 40% Glass Fiber; **Solenoid Valve:** Ferratic Stainless Steel, Austenitic Stainless Steel, Polymide Nylon 6,6, Pro-Opiomelanocortin, EPDM; **Lithium Battery 6V:** Manganese Dioxide, **1,2-Dimethoxyethane**, Propylene Carbonate, Lithium, Lithium Trifluoromethane Sulfonate, Carbon Black, Ethylene Carbonate, Graphite

Living Building Challenge Criteria:

SLV-1003

EXP. 01 MAR 2019

VOC Content: N/A

VOC Emissions: N/A

Declaration Status

LBC Red List Free

LBC Compliant

Declared