

Declare.

Sloan Hybrid Urinal - HYB 1000 Sloan Valve

Final Assembly: Zhangzhou, China

Life Expectancy: 25 Years

End of Life Options: Salvageable/Reusable in its Entirety, Recyclable (97%), Landfill (3%)

Ingredients:

Body: Porcelain, Glaze; Cartridge: ABS Plastic, 2-Octyldodecanol; Cartridge Housing: Stainless Steel, Polypropylene; Waterfree Wall Plaque: Stainless Steel; Mounting Hardware: Stainless Steel; Drain Line Support: Galvanized Steel, Plating Zinc; Nut/Slip Joint: ABS Plastic; Rubber Flange Seal; Clear Inspection Disk: PETE; Hose Clamp: Zinc; Insert Tube: Polypropylene; Hanger Bracket: Stainless Steel; Stamped Retainer Flange: Galvanized Steel, Zinc; Hybrid Air Gap: EPDM, ABS Plastic, Tonval Brass, Stainless Steel, Polypropylene; Base Plate Assembly: Tonval Brass, EPDM, ABS Plastic, Stainless Steel, Thermoplastic Elastomers, Polyphthalamide 40% Glass Fiber; Solenoid Valve: Ferritic Stainless Steel, Austenitic Stainless Steel, Polyimide Nylon 6,6, Pro-Opiomelanocortin, EPDM; Lithium Battery 6V: Manganese Dioxide, 1,2-Dimethoxyethane, Propylene Carbonate, Lithium, Lithium Trifluoromethane Sulfonate, Carbon Black, Ethylene Carbonate, Graphite

Living Building Challenge Criteria:

SLV-2003

VOC Content: N/A

Declaration Status

EXP. 01 APR 2020

VOC Emissions: N/A

- LBC Red List Free
- LBC Compliant
- Declared