

**Declaration Owner**

Sloan Valve Company  
10500 Seymour Avenue, Franklin Park, IL 60131  
P: 847.671.4300 / 800.982.5839 · www.sloan.com

**Product Group**

Washdown Urinals

The washdown urinal products covered by this Environmental Product Declaration (EPD) are based on an average of multiple products.

**Functional Unit**

One washdown urinal used for a period of 20 years.

The scope of this EPD is Cradle-to-Grave.

**EPD Number and Period of Validity**

SCS-EPD-04678  
EPD Valid October 2, 2017 through October 1, 2022  
Version: May 7, 2019

**Product Category Rule**

PCR for Building-Related Products and Services in North America. Adapted for UL Environment from the range of EPDs of the Institute Construction and Environment e.V. (IBU).



**Part A:** Life Cycle Assessment Calculation Rules and Report Requirements. Version 2.0. June 2017.

**Part B:** Requirements on the EPD for Sanitary Ceramics. V1.1. December 2015.

**Program Operator**

SCS Global Services  
2000 Powell Street, Ste. 600, Emeryville, CA 94608  
+1.510.452.8000 | www.SCSglobalServices.com



Declaration Owner:	Sloan Valve Company
Address:	10500 Seymour Avenue, Franklin Park, IL 60131
Declaration Number:	SCS-EPD-04678
Declaration Validity Period:	EPD Valid October 2, 2017 through October 1, 2022
Version Date:	May 7, 2019
Program Operator:	SCS Global Services
Declaration URL Link:	<a href="https://www.scsglobalservices.com/certified-green-products-guide">https://www.scsglobalservices.com/certified-green-products-guide</a>
LCA Practitioner:	Jeremie Hakian, SCS Global Services
LCA Software:	SimaPro v8.3
Independent critical review of the LCA and data, according to ISO 14044 and ISO 14071	<input type="checkbox"/> internal <input checked="" type="checkbox"/> external
LCA Reviewer:	 Tom Gloria, Ph.D., Industrial Ecology Consultants
Part A Product Category Rule:	Life Cycle Assessment Calculation Rules and Report Requirements. Version 2.0. June 2017.
Part A PCR Review conducted by:	Part A PCR review conducted by the SM TAB, tab@sustainableminds.com
Part B Product Category Rule:	Product Group Definition   Requirements on the EPD for Sanitary Ceramics. V1.1. December 2015.
Part B PCR Review conducted by:	Part B PCR review conducted by the SM TAB, tab@sustainableminds.com
Independent verification of the declaration and data, according to ISO 14025 and the PCR	<input type="checkbox"/> internal <input checked="" type="checkbox"/> external
EPD Verifier:	 Tom Gloria, Ph.D., Industrial Ecology Consultants
Declaration Contents:	Product and Company Information.....cover PRODUCT.....2 ADDITIONAL ENVIRONMENTAL INFORMATION.....4 LCA CALCULATION RULES.....5 LCA SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION.....9 LCA RESULTS.....10 LCA INTERPRETATION.....13 REFERENCES.....14
<p><b>Disclaimers:</b> This EPD conforms to ISO 14025, 14040, 14044, and ISO 21930.</p> <p><b>Scope of Results Reported:</b> The PCR requirements limit the scope of the LCA metrics such that the results exclude environmental and social performance benchmarks and thresholds, and exclude impacts from the depletion of natural resources, land use ecological impacts, ocean impacts related to greenhouse gas emissions, risks from hazardous wastes and impacts linked to hazardous chemical emissions.</p> <p><b>Accuracy of Results:</b> Due to PCR constraints, this EPD provides estimations of potential impacts that are inherently limited in terms of accuracy.</p> <p><b>Comparability:</b> The PCR this EPD was based on was not written to support comparative assertions. EPDs based on different PCRs, or different calculation models, may not be comparable. When attempting to compare EPDs or life cycle impacts of products from different companies, the user should be aware of the uncertainty in the final results, due to and not limited to, the practitioner's assumptions, the source of the data used in the study, and the specifics of the product modeled.</p>	

## PRODUCT

### Product Description

Sloan washdown urinals are white vitreous china exchangeable devices that can be connected to a plumbing system to deliver and drain water and are designed to help conserve water. The representative washdown urinal works with 0.125 to 0.5 gpf (gallons per flush)/0.5 to 1.9 Lpf (liters per flush), is made of vitreous china with a ¾" top spud, has a 2" national pipe thread (NPT) outlet flange, and includes a removable strainer, inlet spud, and hanger. Sloan washdown urinals are International Association of Plumbing and Mechanical Officials (IAPMO) certified to meet or exceed American Society of Mechanical Engineers (ASME) A112.19.2 standards, are WaterSense listed by the US Environmental Protection Agency, and meet Americans with Disabilities Act (ADA) guidelines and American National Standards Institute (ANSI) A117.1 requirements.

The following washdown urinals are represented in this EPD:

Washdown Urinal Model Numbers Represented by EPD		
SU7019	SU1209-STG	SU7019
SU7009-STG	SU1209	SU7009-STG
SU7009	SU1019	SU7009
SU1219-STG	SU1009-STG	
SU1219	SU1009	

### Applications

Sloan washdown urinals are installed in restrooms for commercial buildings, airports, stadiums, and the healthcare and hospitality sectors.

### Technical Data

- Minimum flow rate: 18 GPM
- Maximum static pressure: 80 PSI
- Minimum flowing pressure: 25 PSI

### Delivery Status

Sloan washdown urinals are delivered by truck to the customer. Total nominal weight of product with packaging delivered is 34 kg. The nominal dimensions of the representative product are:

**H** 24.38" (619 mm), **W** 14.35" (364 mm), **D** 16.50" (419 mm)

### Material Resources

The material composition and availability of raw material resources of the representative washdown urinal is shown in Table 1.

**Table 1.** Material composition (in % of mass) of the washdown urinal.

Material	Amount (kg)	Percent of Total Weight	Percent Pre-consumer Recycled Content	Percent Post-consumer Recycled Content	Scrap Rate (%)
Clay	13	44%	3.0%	4.0%	15%
Quartz	10	33%	3.0%	4.0%	15%
Feldspar	6.7	22%	3.0%	4.0%	15%
SloanTec™ Hydrophobic Glaze	<0.0010	<0.0010%	0.0%	0.0%	0.0%
<b>Total</b>	<b>30</b>	<b>100%</b>	<b>3.0%</b>	<b>4.0%</b>	<b>15%</b>

The representative washdown urinal weight is based on the average of the minimum (25 kg) and maximum (35 kg) weights of the Sloan washdown urinal products represented by this EPD.

### Product Manufacture

Sloan urinals are manufactured in Hangzhou, China. Raw materials, including clay, quartz, and feldspar are mixed with water and ground thoroughly to form a uniform slip. The slip is screened and magnetically separated in an agitating tank. The ware are then cast in plaster molds and then dried before a glazing process. After glazing, the body is sent for drying and firing. The final products are sorted and packaged for distribution.

### Product Installation

The installation of washdown urinals is completed using hand tools and manual labor, and does not require any electricity or other resources.

### Packaging

The material composition and availability of raw material resources of packaging is shown in Table 2.

**Table 2.** Material composition (in % of mass) of packaging for the washdown urinal.

Material	Amount (kg)	Percent of Total Weight	Percent Pre-consumer Recycled Content	Percent Post-consumer Recycled Content	Scrap Rate (%)
Fluted paper	3.4	70%	5.0%	95%	4.8%
Stainless steel	0.48	10%	5.0%	95%	4.8%
Copper	0.28	5.6%	4.0%	96%	3.9%
Rubber	3.9x10 <sup>-2</sup>	0.81%	1.0%	99%	2.2%
<b>Total</b>	<b>4.2</b>	<b>100%</b>	<b>4.5%</b>	<b>96%</b>	<b>4.4%</b>

### Conditions of Use

It is important to note that water use impacts are assigned to the device that controls water flow to avoid double counting (e.g., flushometer), which is outside the scope of this Environmental Product Declaration. Sloan washdown urinals are assumed to require daily cleaning with 50 mL of 10% HCl solution.

### Environment and Health during use

No release of substances from the washdown urinal to air, soil, or water are expected to occur.

**Reference Service Life**

The Reference Service Life (RSL) of the fixture is assumed to be 20 years.

**Extraordinary Effects**

No environmental or health impacts are expected due to extraordinary effects including fire and/or water damage and product destruction.

**Re-use Phase**

Reuse at end-of-life via collection and processing of washdown urinals is possible but not widely available. It is assumed that no materials are recovered and processed for these purposes.

**Disposal**

It is assumed that fixture products at end-of-life are disposed of in a landfill. Transportation of washdown urinals assumes a 62 miles (100 kilometer) distance to disposal, based on the Plumbing Manufacturers International (PMI) Product Category Rule (PCR) Guidance for Kitchen and Bath Vessel Fixtures. Recycling of packaging materials are based on 2014 statistics regarding municipal solid waste generation and disposal in the United States from the US Environmental Protection Agency. For packaging materials not recycled, it is assumed that 20% are incinerated and 80% go to landfill. Transportation of disposal packaging assumes a 20 mile (32 kilometer) distance based on the US Environmental Protection Agency WARM model.

**Further Information**

Further information on the products covered by this Environmental Product Declaration can be found on the manufacturers' website: [https://www.sloan.com/commercial-bathroom-products/urinals/browse?flush\\_method=washdown](https://www.sloan.com/commercial-bathroom-products/urinals/browse?flush_method=washdown)

## ADDITIONAL ENVIRONMENTAL INFORMATION

Over one billion gallons of water are wasted in the U.S. every year because of inefficient toilets, urinals and faucets. Sloan's high efficiency fixtures and lavatories have been engineered for optimal performance with Sloan flushometers and faucets, and together, these systems conserve an enormous volume of water over the life of the products.

All of the fixtures in this EPD are manufactured in our state of the art, Leadership in Energy and Environmental Design (LEED) Silver, zero municipal water facility in China. This facility was designed to capture rainwater and store it in underground storage tanks where it is then processed to drinking water quality. This water is then used to support the entire engineering center; from test benches and restrooms to showrooms and landscaping

Sloan High-Efficiency Urinals (HEUs) are specifically engineered for commercial facilities that need to accommodate many restroom visitors and conserve water. Sloan HEUs use as little as a 0.125 gallons of water—much less than the 1.0 gpf baseline for urinals.

Any Sloan urinal is available with our SloanTec™ Hydrophobic Glaze. A proprietary glaze that imparts permanent hydrophobic (water-repellent) and oleophobic (oil-repellent) properties to our vitreous china. This permanent glaze lowers the surface energy of vitreous china resulting in the ability of liquid and solid waste to adhere.

## LCA: CALCULATION RULES


### Functional Unit

The functional unit declared in this Environmental Product Declaration is one washdown urinal used for a period of 20 years.



**System Boundary**

The scope of this EPD is cradle-to-grave, including product stage (raw material extraction and processing, transport to the manufacturer, and manufacturing), construction (transport for use and installation), use (cleaning/maintenance, repair, replacement, and refurbishment), and end-of-life (de-construction/demolition, transport, waste processing, and disposal). The benefits and loads beyond the system boundary for reuse, recovery, and recycling potential (module D), are not included in this study. The diagram below is a representation of the most significant contributions to the life cycle of the washdown urinal products.



## Estimates and Assumptions

The assessment relied on several assumptions, described below.

- Representative inventory data from Ecoinvent, version 3.3, was used to reflect the energy mix for electricity use at the manufacturing facility.
- Distances and mode from distribution center to installation site is based on the PMI PCR Guidance for Kitchen and Bath Vessel Fixtures.
- Distance and mode from building site to waste processing is based on the PMI PCR Guidance for Kitchen and Bath Vessel Fixtures.
- Inventory data for unit processes in the system were modeled with data taken from Ecoinvent, version 3.3.

## Cut-off Criteria

The cut-off criteria for including or excluding materials, energy, and emissions data from the study are in accordance with the PCR and are listed below.

- Mass and energy flows that consist of less than 1% may be omitted from the inventory analysis
- Cumulative omitted mass or energy flows shall not exceed 5%

## Background Data

Unit processes are developed with SimaPro 8.3 software, drawing upon data from multiple sources. Primary data were provided by the manufacturer for their processes and upstream transport. The primary sources of secondary life cycle inventory data are from Ecoinvent, version 3.3.

**Table 3.** Data sources used for the life cycle assessment.

Flow	Dataset	Data Source	Publication Date
<b>Product Materials</b>			
Clay	Clay {RoW}   clay pit operation   Alloc Rec, U	Ecoinvent	2016
Silica	Silica sand {RoW}   production   Alloc Rec, U	Ecoinvent	2016
Feldspar	Feldspar {RoW}   production   Alloc Rec, U	Ecoinvent	2016
<b>Packaging</b>			
Fluted paper	Linerboard {RoW}   treatment of recovered paper to, testliner   Alloc Rec, U	Ecoinvent	2016
Copper	Metal working, average for copper product manufacturing {RoW}   processing   Alloc Rec, U	Ecoinvent	2016
Stainless steel	Steel, chromium steel 18/8 {RoW}   steel production, electric, chromium steel 18/8   Alloc Rec, U; Metal working, average for chromium steel product manufacturing {RoW}   processing   Alloc Rec, U	Ecoinvent	2016
Rubber	Injection moulding {RoW}   processing   Alloc Rec, U	Ecoinvent	2016
<b>Ancillary Materials in Manufacturing</b>			
Gypsum	Gypsum, mineral {GLO}   market for   Alloc Rec, U	Ecoinvent	2016
<b>Electricity/Heat/Resources for Manufacturing</b>			
Electricity	Electricity, medium voltage {CN}   market group for   Alloc Rec, U	Ecoinvent	2016
Natural Gas	Heat, district or industrial, natural gas {CN}   heat production, natural gas, at industrial furnace >100kW   Alloc Rec, U	Ecoinvent	2016
Water	Tap water {RoW}   market for   Alloc Rec, U	Ecoinvent	2016
<b>Cleaning Materials</b>			
10% HCl solution	Hydrochloric acid, without water, in 30% solution state {RoW}   market for   Alloc Rec, U; Water, deionised, from tap water, at user {RoW}   production   Alloc Rec, U	Ecoinvent	2016
<b>Transportation</b>			
Road	Transport, freight, lorry 16-32 metric ton, EURO4 {GLO}   market for   Alloc Rec, U	Ecoinvent	2016
Ship	Transport, freight, sea, transoceanic ship {GLO}   market for   Alloc Rec, U	Ecoinvent	2016
Waste	Municipal waste collection service by 21 metric ton lorry {RoW}   market for municipal waste collection service by 21 metric ton lorry   Alloc Rec, U	Ecoinvent	2016

CN: China; RoW: Rest-of-World; GLO: Global; U: Unit process; Alloc Rec: Allocation, recycled content.



**Data Quality**

Data Quality Parameter	Data Quality Discussion
<b>Time-Related Coverage</b> Age of data and the minimum length of time over which data is collected	Manufacturer data (primary data) are based on 2016 annual production, respectively. Representative datasets (secondary data) used for upstream and background processes are generally less than 5 years old. All primary data used represented an average of at least one year's worth of data collection.
<b>Geographical Coverage</b> Geographical area from which data for unit processes is collected to satisfy the goal of the study	The data used in the analysis provide the best possible representation available with current data. Representative data used in the assessment are representative of China, Global, or "Rest-of-World" (average for all countries in the world with uncertainty adjusted). Datasets chosen are considered sufficiently similar to actual processes.
<b>Technology Coverage</b> Specific technology or technology mix	For the most part, data are representative of the actual technologies used for processing, transportation, and manufacturing operations.
<b>Precision</b> Measure of the variability of the data values for each data expressed (e.g. variance)	Precision of results are not quantified due to a lack of data. Data collected for operations were typically averaged for one year and over multiple operations, which is expected to reduce the variability of results.
<b>Completeness</b> Percentage of flow that is measured or estimated	Except where noted, the LCA model included all known mass and energy flows. In some instances, surrogate data used to represent upstream operations (processing of reclaimed packaging and product materials) may be missing some data which is propagated in the model. No known processes or activities contributing to more than 10% of the total environmental impact for each indicator are excluded. In total, these missing data represent less than 5% cumulative omitted mass or energy flows from the inventory analysis.
<b>Representativeness</b> Qualitative assessment of the degree to which the data set reflects the true population of interest (i.e. geographical coverage, time period and technology coverage)	Data used in the assessment represent typical or average processes as currently reported from multiple data sources, and are therefore generally representative of the range of actual processes and technologies for production of these materials. Considerable deviation may exist among actual processes on a site-specific basis; however, such a determination would require detailed data collection throughout the supply chain back to resource extraction. Some proxy datasets are used to represent unit processes due to the lack of data available (processing of reclaimed packaging materials).
<b>Consistency</b> Qualitative assessment of whether the study methodology is applied uniformly to the various components of the analysis	The consistency of the assessment is considered to be high. Data sources of similar quality and age are used and are all sourced from Ecoinvent. Different portions of the product life cycle are equally considered.
<b>Reproducibility</b> Qualitative assessment of the extent to which information about the methodology and data values would allow an independent practitioner to reproduce the results reported in the study	Based on the description of data and assumptions used, this assessment would be reproducible by other practitioners. All assumptions, models, and data sources are documented.
<b>Sources of the Data</b> Description of all primary and secondary data sources	For manufacturing, packaging, and upstream transport, and transport of final product to distribution center, primary data were provided by the manufacturer. Distances and modes from distribution center to installation site is based on Table 5 of PMI PCR Guidance for Kitchen and Bath Vessel Fixtures. All other secondary data were taken from Ecoinvent, version 3.3.
<b>Uncertainty of the Information</b> Uncertainty related to data, models, and assumptions	Uncertainty related to the product materials and packaging is low. Data for upstream operations relied upon use of existing representative datasets. These datasets contained relatively recent data (<5 years), but lacked specific geographical representativeness. Uncertainty related to the impact assessment methods used in the study are high. The impact methods required by the PCR include impact potentials, which lack characterization of providing and receiving environments or tipping points.

**Period under Review**

The period of review is calendar year 2016.

**Allocation**

Manufacturing resource use was allocated to the products based on mass. The representative washdown urinal includes recycled content, which are allocated using the recycled content allocation method, also known as the 100-0 cut off method. Impacts from transportation were allocated based on the mass of material and distance transported.

**Comparability**

The PCR this EPD is based on was not written to support comparative assertions. EPDs based on different PCRs, or different calculation models, may not be comparable. When attempting to compare EPDs or life cycle impacts of products from different companies, the user should be aware of the uncertainty in the final results, due to and not limited to, the practitioner's assumptions, the source of the data used in the study, and the specifics of the product modeled.

## LCA: SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

The following provides a brief overview of the modules included in the product system for Sloan® washdown urinal products.

**Module A1: Raw material extraction and processing, processing of secondary material inputs**

This stage includes extraction of virgin materials and reclamation of non-virgin feedstock. This includes the extraction of all raw materials, including the transport to the manufacturing site. Resource use and emissions associated with both extraction and processing of the raw materials are included.

**Module A2: Transportation**

The impacts associated with the transport of the processed raw materials to the manufacturing facility.

**Module A3: Manufacture**

This stage includes all the relevant manufacturing processes and flows, including the impacts from energy use and emissions at the manufacturing facility. Production of capital goods, infrastructure, manufacturing equipment, and personnel-related activities are not included. This stage also includes the production of packaging and ancillary materials.

**Module A4: Transportation & Delivery to the site**

This module includes the impacts associated with transportation of finished washdown urinal to US based distribution centers and the subsequent delivery to the installation site. Distribution of the washdown urinal to the point of installation assumed a transport distance of 10,600 km by ocean freighter and 3,335 km by diesel truck. The gross mass transported is 34 kg, which includes the product and its packaging.

**Module A5: Construction & Installation**

Installation is performed manually and any ancillary material used is considered negligible over the life cycle of the product. This module also includes the transport and disposal of packaging. Transport of packaging to disposal assumed a distance of 32 km by diesel truck. The gross mass of packaging transported is 4.2 kg.

**Module B1: Normal use of the product**

No release of substances from the washdown urinal to indoor or outdoor air, soil, or water are expected to occur.

**Module B2: Maintenance**

The maintenance stage includes cleaning. The cleaning type, amount, and frequency assumptions are derived from the PMI PCR Guidance for Kitchen and Bath Vessel Fixtures. Daily cleaning with 50 mL of 10% HCl solution is assumed. This is equivalent to 7,300 cleanings or a total of 383 kg of cleaning solution over the 20 year RSL.

**Module B3-B5: Repair, Replacement, and Refurbishment**

Any repair of the installed product is typically performed manually and any ancillary material used is considered to be negligible. There is no anticipated replacement or refurbishment of the installed product over the declared reference service life.

**Module B6: Operational Energy Use**

This module is not applicable because washdown urinals do not require energy during the operation of the product.

**Module B7: Operational Water Use**

Water use impacts are assigned to the device that controls water flow rate (e.g., flushometer) to avoid double counting, which is outside the scope of this Environmental Product Declaration.

**Module C1-C4: End-of-Life**

Deconstruction and dismantling of the installed product is performed manually with hand tools and does not require any resource use. Transport of the installation product from building site to waste processing is assumed to be 100 km by diesel truck and is derived from the PMI PCR Guidance for Kitchen and Bath Vessel Fixtures. Waste processing of washdown urinals for reuse, recycling, and energy recovery is possible but not widely available. As such, it is assumed that no materials are collected separately, recovered, and processed for these purposes. It is assumed that the product at end-of-life is disposed of in a landfill, equivalent to 30 kg of inert landfill waste.

**LCA: RESULTS**

The system boundary is cradle-to-grave and includes resource extraction and processing, product manufacture and assembly, distribution/transport, use and maintenance, and end-of-life. The diagram below illustrates the life cycle stages included in this EPD.

Product Stage			Construction Process Stage		Use Stage							End-of-life Stage				Benefits and loads beyond the system boundary
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw material extraction and processing	Transport to manufacturer	Manufacturing	Transport	Construction - installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, recovery and/or recycling potential
X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MND

X = Included in system boundary; MND = Module not declared

The choice of categories and indicators used in the assessment are taken from the PCR. Impact category indicators are estimated using TRACI 2.1. All results are calculated using SimaPro, version 8.3, and values are rounded to two significant digits. Results reported as *neg* represent “negligible”. In accordance with Part A of the PCR, the average coefficient of variation across all impact categories for washdown urinal products is 5.6%.

**Table 4.** List of impact categories, impact category acronyms, LCIA method, and units for reporting of results.

Impact Category	Acronym	LCIA Method	Reporting Unit
Global Warming Potential	GWP	IPCC 2013, 100 years	Kilograms CO <sub>2</sub> eq
Acidification Potential	AP	TRACI 2.1	Kilograms SO <sub>2</sub> eq
Smog	SP	TRACI 2.1	Kilograms O <sub>3</sub> eq
Eutrophication Potential	EP	TRACI 2.1	Kilograms N eq
Ozone Depletion Potential	ODP	TRACI 2.1	Kilograms CFC-11 eq
Fossil Fuel Depletion	FFD	TRACI 2.1	MJ surplus

**Table 5.** Impact category results reported by for washdown urinals maintained for 20 years.

Module	GWP (kg CO <sub>2</sub> eq)	ODP (kg CFC-11 eq)	AP (kg SO <sub>2</sub> eq)	EP (kg N eq)	SP (O <sub>3</sub> eq)	FFD (MJ surplus)
Total	160	4.4x10 <sup>-5</sup>	0.84	0.50	12	210
	100%	100%	100%	100%	100%	100%
A1	0.78	6.4x10 <sup>-8</sup>	5.3x10 <sup>-3</sup>	2.0x10 <sup>-3</sup>	7.4x10 <sup>-2</sup>	0.91
	0.49%	0.15%	0.63%	0.40%	0.63%	0.43%
A2	2.3	4.3x10 <sup>-7</sup>	1.1x10 <sup>-2</sup>	2.6x10 <sup>-3</sup>	0.25	5.1
	1.5%	1.0%	1.3%	0.53%	2.2%	2.4%
A3	47	1.5x10 <sup>-6</sup>	0.18	7.1x10 <sup>-2</sup>	1.3	84
	29%	3.4%	21%	14%	11%	40%
A4	15	2.7x10 <sup>-6</sup>	0.14	2.0x10 <sup>-2</sup>	2.5	32
	9.3%	6.1%	16%	4.0%	21%	15%
A5	1.0	3.4x10 <sup>-8</sup>	1.3x10 <sup>-3</sup>	5.2x10 <sup>-3</sup>	3.1x10 <sup>-2</sup>	0.41
	0.64%	0.078%	0.15%	1.0%	0.26%	0.19%
B1	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
B2	90	3.8x10 <sup>-5</sup>	0.49	0.39	6.9	80
	56%	88%	58%	79%	59%	38%
B3	neg	neg	neg	neg	neg	neg
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
B4	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
B5	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
B6	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
B7	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
C1	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
C2	3.9	7.1x10 <sup>-7</sup>	2.3x10 <sup>-2</sup>	3.2x10 <sup>-3</sup>	0.62	8.3
	2.4%	1.6%	2.7%	0.64%	5.3%	3.9%
C3	0.0	0.0	0.0	0.0	0.0	0.0
	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
C4	0.18	6.1x10 <sup>-8</sup>	1.6x10 <sup>-3</sup>	3.4x10 <sup>-4</sup>	3.7x10 <sup>-2</sup>	0.75
	0.11%	0.14%	0.19%	0.068%	0.32%	0.36%

The key life cycle inventory data parameters are taken from the PCR, which include resource use, output flows, and waste categories. All results are calculated using SimaPro software, version 8.3, and values are rounded to two significant digits. Results reported in MJ are calculated using higher heating values. Results reported as *INA* represent “indicators not assessed”.

**Table 6.** List of key life cycle inventory parameters, parameter acronyms, and units for reporting of results.

Key Life Cycle Inventory Parameter	Acronym	Reporting Unit
Renewable primary energy as energy carrier	PERE	Megajoules
Renewable primary energy resources as material utilization	PERM	Megajoules
Total use of renewable primary energy resources	PERT	Megajoules
Non-renewable primary energy as energy carrier	PENRE	Megajoules
Non-renewable primary energy as material utilization	PENRM	Megajoules
Total use of non-renewable primary energy resources	PENRT	Megajoules
Use of secondary material	SM	Kilograms
Use of renewable secondary fuels	RSF	Megajoules
Use of non-renewable secondary fuels	NRSF	Megajoules
Use of net fresh water	FW	Cubic meters
Hazardous waste disposed	HWD	Kilograms
Non-hazardous waste disposed	NHWD	Kilograms
Radioactive waste disposed	RWD	Kilograms
Components for re-use	CRU	Kilograms
Materials for recycling	MFR	Kilograms
Materials for energy recovery	MER	Kilograms
Exported electric energy	EEE	Megajoules
Exported thermal energy	EET	Megajoules

**Table 7.** Resource use results for washdown urinals maintained for 20 years.

Module	PERE (MJ)	PERM (MJ)	PERT (MJ)	PENRE (MJ)	PENRM (MJ)	PENRT (MJ)	SM (kg)	RSF (MJ)	NRSF (MJ)	FW (m <sup>3</sup> )
Total	143	0.0	143	INA	INA	2,200	0.0	neg	neg	11
A1	0.50	0.0	0.50	INA	INA	9.7	0.0	neg	neg	4.8x10 <sup>-2</sup>
A2	0.46	0.0	0.46	INA	INA	38	0.0	neg	neg	2.6x10 <sup>-2</sup>
A3	17	0.0	17	INA	INA	680	6.3	neg	neg	0.72
A4	3.6	0.0	3.6	INA	INA	240	0.0	neg	neg	0.20
A5	2.9x10 <sup>-2</sup>	0.0	2.9x10 <sup>-2</sup>	INA	INA	3.0	0.0	neg	neg	2.2x10 <sup>-3</sup>
B1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B2	120	0.0	120	INA	INA	1,200	0.0	neg	neg	10
B3	neg	0.0	neg	neg	neg	neg	neg	neg	neg	Neg
B4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C2	0.25	0.0	0.25	INA	INA	59	0.0	neg	neg	2.0x10 <sup>-2</sup>
C3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C4	0.14	0.0	0.14	INA	INA	5.5	0.0	neg	neg	8.1x10 <sup>-3</sup>

**Table 8.** Waste and outflows for washdown urinals maintained for 20 years.

Module	HWD (kg)	NHWD (kg)	RWD (kg)	CRU (kg)	MFR (kg)	MER (kg)	EEE (MJ)	EET (MJ)
Total	4.1x10 <sup>-3</sup>	57	8.5x10 <sup>-4</sup>	0.0	neg	neg	neg	neg
A1	1.9x10 <sup>-5</sup>	1.2	5.5x10 <sup>-6</sup>	0.0	neg	neg	neg	neg
A2	2.1x10 <sup>-5</sup>	1.7	4.1x10 <sup>-5</sup>	0.0	neg	neg	neg	neg
A3	5.5x10 <sup>-4</sup>	3.2	2.9x10 <sup>-5</sup>	0.0	neg	neg	neg	neg
A4	1.3x10 <sup>-4</sup>	7.8	2.5x10 <sup>-4</sup>	0.0	neg	neg	neg	neg
A5	1.2x10 <sup>-6</sup>	0.71	3.2x10 <sup>-6</sup>	0.0	neg	neg	neg	neg
B1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B2	3.3x10 <sup>-3</sup>	8.1	4.4x10 <sup>-4</sup>	0.0	neg	neg	neg	neg
B3	neg	neg	neg	neg	neg	neg	neg	neg
B4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
B7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C2	1.9x10 <sup>-5</sup>	0.24	6.6x10 <sup>-5</sup>	0.0	neg	neg	neg	neg
C3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
C4	3.6x10 <sup>-6</sup>	34	5.7x10 <sup>-6</sup>	0.0	neg	neg	neg	neg

## LCA: INTERPRETATION

The interpretation phase conforms to ISO 14044 with further guidance from the International Reference Life Cycle Data System (ILCD) General Guide for Life Cycle Assessment. The interpretation included the use of evaluation and sensitivity checks to steer the iterative process during the assessment, and a final evaluation including completeness, sensitivity, and consistency checks, at the end of the study.

For washdown urinals, the major hotspot in the supply chain lies in the maintenance of the fixture, specifically cleaning (Module B2), followed by manufacturing (Module A3), primarily from the use of natural gas.

## REFERENCES

1. IPCC, 2013: Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change [Stocker, T.F., D. Qin, G.-K. Plattner, M. Tignor, S.K. Allen, J. Boschung, A. Nauels, Y. Xia, V. Bex and P.M. Midgley (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 1535 pp, doi:10.1017/CBO9781107415324.
2. ISO 14025:2006 Environmental labels and declarations – Type III environmental declarations – Principles and Procedures.
3. ISO 14040: 2006 Environmental Management – Life cycle assessment – Principles and framework.
4. ISO 14044: 2006 Environmental Management – Life cycle assessment – Requirements and Guidelines.
5. ISO 21930: 2007 Sustainability in building construction – Environmental declaration of building products.
6. Life Cycle Assessment of Sanitary Fixtures. SCS Global Services Final Report. Prepared for Sloan Valve Company. September 2017.
7. Plumbing Manufacturers International Product Category Rule Guidance for Kitchen and Bath Vessel Fixtures. <https://www.safeplumbing.org/index/product-category-rules-pcr-documents/product-category-rules-document-for-kitchen-and-bath-vessel-fixtures>.
8. SCS Type III Environmental Declaration Program: Program Operator Manual. V10.0 April 2019. SCS Global Services.
9. Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI). Dr. Bare, J., <http://www.epa.gov/nrmrl/std/traci/traci.html>
10. UL. Product Category Rules for Building-Related Products and Services. Part A: Life Cycle Assessment Calculations Rules and Report Requirements. Version 2. Standard 10010. June 28, 2017.
11. UL. PCR Guidance-Texts for Building-Related Products and Services. From the range of Environmental Product Declaration of UL Environment. Part B: Requirements on the EPD for Sanitary ceramics. Version 1.1, 2015.
12. US EPA. Advancing Sustainable Materials Management: 2014 Fact Sheet. Assessing Trends in Material Generation, Recycling, and Disposal in the United States. November 2015.
13. US EPA. WARM Model Transportation Research - Draft. Memorandum from ICF Consulting to United States Environmental Protection Agency. September 7, 2004.
14. Wernet, G., Bauer, C., Steubing, B., Reinhard, J., Moreno-Ruiz, E., and Weidema, B., 2016. The ecoinvent database version 3 (part I): overview and methodology. The International Journal of Life Cycle Assessment, [online] 21(9), pp.1218–1230. Available at: <http://link.springer.com/10.1007/s11367-016-1087-8>.



For more information contact:

**Sloan Valve Company**

10500 Seymour Avenue, Franklin Park, IL 60131  
P: 847.671.4300 | 800.982.5839 | [www.sloan.com](http://www.sloan.com)



**SCS Global Services**

2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA  
Main +1.50.452.8000 | fax +1.510.452.8001